

SIGN INSTALL GUIDE

METHOD: STUD MOUNTS (THREADED RODS)

Sign installation has never been easier!

This step-by-step guide along with our handy mounting templates makes the process quick and easy.

(it will save you a bunch of money too!)



816.800.9444



info@lettersandsigns.com



11447 Strang Line Rd. Lenexa, KS 66215

What you will need:

- Signage and/or Letters
- Mounting Template (included with order)
- Stud Mounts/Threaded Rods (included with order)
- Drill
- Drill Bit (3/16")
- Tape Measure
- Level
- Masking Tape or Painter's Tape
- Clear Silicone

Before you get started:

Make sure your wall is CLEAN and DRY before installing the signage

NOTE: If installing on Stone or Brick use a 3/16" Masonry Drill Bit and Hammer Drill



STEP 1

Plan & Prep Sign Location

If centering the sign, use a tape measure to find and lightly mark the wall's center point.

If not centering, hold the template up to "pre-view" placement and choose the ideal location.

Wipe the area with a clean, non-abrasive cloth so the template tape sticks well.

STEP 2

Position the Template

Lightly tape the template to the wall using masking or painter's tape. Use the template's center marks/notches (if included) to help align it.

TIP: Don't fully tape down the template yet - you may adjust it in the next step



STEP 3

Level Template & Apply More Tape

Ensure the template is level on the wall.

Then apply more tape. Ensure the template is taped tight and flat against the wall.

STEP 4

Drill Holes (through the template)

Using a drill bit slightly larger than the stud diameter (usually 3/16" bit), drill straight through the paper template at each stud mark and into the wall.

IMPORTANT:

Keep the drill perpendicular to the wall so the holes are straight and studs slide in easily.



STEP 5

Attach Studs

Hand-Tighten the stud mounts (threaded rods) into the holes on the back of letters. Slide stand-offs (if included with your order) over studs.

IMPORTANT: Do not overtighten. Just hand-tighten until the feel secure and not wobbly.

STEP 6

Test Fit a Few Letters

Carefully remove the template and clean dust from the holes (vac/brush works great).

Then do a quick dry run:

Place one or two letters onto the wall (no silicone yet) to confirm everything lines up. Adjust any tight holes as needed.





STEP 7

Fill Holes with Silicone

Fill each drilled hole partially with silicone (about 1/3 full is usually enough). You want coverage—not a hole overflowing with sealant. This helps lock the studs in place and reduces moisture exposure.

STEP 8

Apply Silicone to Studs

Apply a small dab/light coat of silicone to the tips of the studs (or the portion that will sit inside the wall).

IMPORTANT: Less is more. Too much silicone can squeeze out around the letter edges.



STEP 9

Mount The Letters

Starting with one letter, align the studs with the holes and press the letter straight into place until it sits flush (or until spacers/standoffs touch the wall, if your set uses them).

Repeat for each letter.



THAT'S IT!

Now take a step back and enjoy your sign.

Do a happy dance, give yourself a pat on the back, pop champagne! Whatever it is - you deserve it!

We would love to see pictures of your sign.

Use the QR Code or email below to send us some.

If you have any questions please contact us

816 - 800 - 9444

info@lettersandsigns.com